

## DESCRIPTION

DESCRIPTION			MEGA
Surface			X PUR scuff-resistant surface
Backing			Combined closed cell foam system
Thickness	mm	EN ISO 24346	10,3
Top layer	mm	EN ISO 24340	1,2
Weight	g/m <sup>2</sup>	EN ISO 23997	5200
Width	m	EN ISO 24341	2
Standard roll length	kg/m <sup>2</sup>	EN ISO 24341	15 ± 10%

## CLASSIFICATION

Product specification		EN 14904	Vinyl indoor sports floor (category P3)
Impact sound insulation	dB	EN ISO717-2	22
Thermal resistance	m <sup>2</sup> K/W	EN 685	0,1
Reaction to fire	-	EN 13501	C <sub>fl</sub> -s1



## SPORT PROPERTIES

Friction	-	EN 13036-4	80-110
Shock absorption	%	EN 14808	≥ 45 (P3)
Vertical deformation	mm	EN 14809	2,0
Ball rebound	%	EN 12235	96
Specular gloss	%	EN 2813	< 30

## TECHNICAL CHARACTERISTICS

Dimensional stability	%	EN ISO 23999	± 0,2
Indentation resistance	mm	EN 1516	< 0,5
Resistance to rolling load	N	EN 1569	1500
Colour fastness	-	EN 13036-4	6
Chemical resistance	-	EN ISO 26987	- no change
Abrasion resistance	mg/1000 cycles	EN ISO 5470-1	< 250

## OTHERS



## GRABOPLAST LTD.

H-9023 Győr, Fehérvári út. 16/b. Telefon: (+36) 96 506-100  
 instagram.com/graboplast | facebook.com/graboplast  
 www.grabo1905.com

