

GRABO

1905

DOMUS SPC COMPACT

Technical datasheet

Technical parameter	Standard	Unit	Result
DESCRIPTION			
Construction	Rigid modular flooring with SPC core		
Total thickness	EN ISO 24346	mm	3,5
Wear layer thickness	EN ISO 24340	mm	0,3
Plank size	EN ISO 24341	mm	180 x 1250
Total weight	EN ISO 23997	kg/m ²	6,8
CLASSIFICATION			
European classification	EN 685	class	23/31
PERFORMANCE			
Abrasion group	MSZ EN 660-2	class	T
Residual indentation	EN ISO 24343	max. mm	0,1
Dimensional stability	EN ISO 23999	max. %	0,25
Wear resistance IP method A	EN 13329	min. cycles	1200
Fire resistance	EN 13501-1	class	Bfl-s1
Slip resistance	DIN 51130		R10
	EN 13893		DS
Chemical resistance	EN ISO 26987		✓
Light fastness	EN 20105 B02	grade	6
Locking			i4F
Surface treatment			SILVER KNIGHT iGUARD
VOC emission	ISO 16000		✓
Environmental attributes			Phthalate, Solvent and Heavy metal free product
Content of PCP	EN 12673		does not contain
Formaldehyde emission	ENV 717-1		E1 (no emission)

GRABOPLAST Ltd.

H-9023 Győr, Fehérvári út 16/b tel.: (36) 96 506 100
 info@grabo1905.com www.grabo1905.com